TELTONIKA | Networks



CONNECTIVITY

4G/LTE (Cat 4), 3G, 2G

RUTOS

Easy to use, secure and feature rich OpenWRT based operating system

COMPACTNESS

Small size, easy installation

DURABILITY

Rugged aluminum housing

9-30V

Wide range of supported power supply voltages

RMS

Compatible with Teltonika Remote Management System



CONNECTIVITY

4G/LTE (Cat 1), 3G, 2G

1/0

Wide range of multiple Inputs/Outputs for remote monitoring and control

COMPACTNESS

Small size, easy installation

DURABILITY

Rugged aluminum housing

9-30

Wide range of supported power supply voltages

RMS

Compatible with Teltonika Remote Management System



CONNECTIVITY

4G/LTE (Cat 1), 3G, 2G

SERIAL PORT

Equipped with RS232 for serial communication

COMPACTNESS

Small size, easy installation

DURABILITY

Rugged aluminum housing

9-30V

Wide range of supported power supply voltages

RMS

Compatible with Teltonika Remote Management System



CONNECTIVITY

4G/LTE (Cat 1), 3G, 2G

SERIAL PORT

Equipped with RS485 for serial communication

COMPACTNESS

Small size, easy installation

DURABILITY

Rugged aluminum housing

9-30V

Wide range of supported power supply voltages

RMS

Compatible with Teltonika Remote Management System