TELTONIKA | Networks

CONNECTIVITY
4G/LTE (Cat 4), 3G, 2G

DURABILITY
Rugged aluminum housing

RUTOS
Easy to use, secure and feature rich OpenWRT based operating system

9-30V
Wide range of supported power supply voltages

COMPACTNESS
Small size, easy installation

RMS
Compatible with Teltonika Remote Management System

CONNECTIVITY
4G/LTE (Cat 1), 3G, 2G

DURABILITY
Rugged aluminum housing

I/O
Wide range of multiple Inputs/Outputs for remote monitoring and control

9-30V
Wide range of supported power supply voltages

COMPACTNESS
Small size, easy installation

RMS
Compatible with Teltonika Remote Management System

CONNECTIVITY
4G/LTE (Cat 1), 3G, 2G

DURABILITY
Rugged aluminum housing

SERIAL PORT
Equipped with RS232 for serial communication

9-30V
Wide range of supported power supply voltages

COMPACTNESS
Small size, easy installation

RMS
Compatible with Teltonika Remote Management System

CONNECTIVITY
4G/LTE (Cat 1), 3G, 2G

DURABILITY
Rugged aluminum housing

SERIAL PORT
Equipped with RS485 for serial communication

9-30V
Wide range of supported power supply voltages

COMPACTNESS
Small size, easy installation

RMS
Compatible with Teltonika Remote Management System