







Product Change Notification

PCN number: PCN_TRB245_2022_11_25_EN_CIEL		Date: 2022.11.25
Change description		
Change type	External/visual	
Detailed description	<p>The device's unique default password will be added to the bottom engraving/labeling. The formatting for the remaining information on the labeling/engraving will be adjusted, and the Fira font will be used instead of Arial. The device's unique default password information will also be added to the QR code Information displayed after scanning QR code with syntax: SN:{{SN}};I:{{IMEI}};M:{{MAC}};U:admin;PW:{{DEVICEPASSWORD}};B:{{BATCH}};</p> <p>From the device top engraving/labeling, the previously relevant authentication information text will be removed: User/Pass: admin/admin01.</p> <p>The labeling on the product packaging will stay unchanged.</p>	
	Old top engraving/labeling:	New top engraving/labeling:
		
	Old bottom engraving/labeling:	New bottom engraving/labeling:
<div> <div> SERIAL 999999999 Batch no: 999  IMEI 999999999999999 LAN MAC AABCCDDEEFF </div> <div>  </div> </div> <div> <div> SERIAL 999999999 BATCH NO: 999  IMEI 999999999999999 LAN MAC AABCCDDEEFF USERNAME admin PASSWORD 99999999 </div> <div>  </div> </div>		
Change reasons	To accommodate the change from the standard default password to a unique default password for each device.	

Affected products information	
All TRB245 ***** product codes are affected. No product code changes.	
Upcoming change date	2022, week 50

Change impact	
Risk Assessment	Changes to top labeling/engraving. Device's unique default password will be present on the product itself. This might impact marketing materials due to changing contents of the bottom informational engraving/labeling.
Suggested action taken	No implementation plan needed.

Acknowledgement of PCN Receipt	
If no feedback is received within two weeks after the issue date of this notification - Teltonika may accept that this change has been tacitly accepted and can implement the change as indicated above.	