

# Project software

## FW downloads

This page contains various branch firmware versions for Teltonika Networks devices.

## RUT955

### [RUT9\\_R\\_00.07.00.811](#) | 2021.12.15

- **New features**

- New, RUTX-like WebUI style
- New WebUI based on Vue.js 2.6.12
- RutOS updated to OpenWrt 19.07.7 base
- DNP3 Master and DNP3 Oustation
- 'Restore to user's defaults' SMS Utilities rule
- DHCP Relay AT command

- **Improvements**

- Added delay option to MODBUS TCP Master
- Updated firewall to release 3
- Updated kernel to version 4.14.221
- Updated uhttpd to version 2020-10-01
- Updated xtables-addons to release 9
- Updated mwan to version 2.8.14
- Updated pcre to version 8.44
- Updated curl to version 7.74
- Updated sqlite to version 3.33
- Updated ncurses to version 6.2
- Updated OpenSSL to version 1.1.1k
- Added full MODBUS register address expansion specifier for Data to Server
- Added full MODBUS register address legend
- Added Client ID option for the MQTT protocol in Data to Server
- Improved Data to Server sleeping accuracy
- Improved Data to Server username validation; now space is allowed
- Added firmware version OID to the SNMP service
- Added IP address family option field to the SNMP page
- Added SNMPv6 section to the SNMP Communities page
- Renamed the 'System -> Users' page to 'System -> System Users'
- Moved password changing option to the 'System -> System Users' page
- Switched to ar8216 driver
- Added IPsec XAUTH support
- Improved OpenVPN updown, init scripts to write info about instance in JSON
- Added AES-256-GCM encryption support to OpenVPN
- Added extra configuration parameters to DMVPN
- Added PSK conversion to DMVPN and single PSK types
- Improved Package Manager package installation, deletion and dependencies

- Improved Package Manager download process over FOTA
- Added new Input/Output values manageable over RMS
- Added IPv6 traffic logging
- Made 'Network -> Failover' and 'Network -> Interfaces' page data draggable on multiple browsers
- Added Input/Output Post/Get URL parameter t\_time changing delay and time to seconds or milliseconds
- Added message storage management by config value
- Improved QMI error handling and status tracking
- Turned on modem in preinit for correct power-on sequence
- Added Post/Get feature to turn mobile data on/off
- Added the possibility to use 2gonly/3gonly/4gonly arguments for cellular service command alongside current 2g/3g/lte arguments
- Added "Phone number" and "Message" fields for "Send SMS" option
- Added "Host to ping from SIM1" and "Host to ping from SIM2" fields
- Added support for multiple USB to Serial adapters
- Added option to send SMS warning messages to Hotspot users authenticated with SMS OTP when specified amount of data is used up
- Added "send analog input" option to TAVL settings

#### • Fixes

- Added glib2 patch to fix CVE-2019-13012 vulnerability
- Added ntfs-3g patch to fix CVE-2019-9755 vulnerability
- Added WolfSSL patch to fix CVE-2021-3336 vulnerability
- Added Busybox patch to fix CVE-2018-1000500 vulnerability
- Added netifd, odhcp6c IPv6 routing loop on point-to-point links patches to fix CVE-2021-22161 vulnerability
- Fixed Android clients IPsec MTU/MSS size
- Fixed wrong IPsec DPD value saving
- Changed IPsec PSK maximum length to 128 symbols
- Fixed SSTP remaining up after package removal
- Fixed DMVPN crypto\_proposal write to config
- Fixed I/O Juggler's SMS sending to correct group
- Fixed I/O Scheduler's relay state issue
- Added I/O direction check while changing IOs via I/O Post/Get
- Fixed float endianness mismatch on some devices MODBUS TCP Master, MODBUS Serial Master
- Fixed UPnP issue that caused config changes to apply only after service restart
- Fixed WebUI files caching when upgrading firmware
- Fixed WebUI date display format
- Fixed MODBUS returning incomplete MAC address data
- Fixed GPS time synchronization for DST regions
- Fixed depleting IPv6 RA timeout when the ISP doesn't send RA updates
- Added "Transaction timed out" error handling
- Fixed PPPOE connection loss when wrong session PADT packet arrives
- Added gcont object tracking and info update if this service is restarted
- Fixed default SMS storage
- Fixed SMS warning sending after Mobile Data Limit change
- Fixed DHCP relaying over mobile networks
- Changed PIN code maximum length to 8 symbols
- Fixed 'I/O status' message to include correct Input/Output name based on info in ubus

ioman objects

- Fixed 'Over IP' serial type's UDP issue in client mode
- Fixed DLNA connections count total in statistics page
- Fixed WiFi Hotspot's Walled Garden issues
- Fixed WiFi Hotspot data logging issues
- Fixed P2P group information processing vulnerability in wpa\_suplicant
- Added validation to Walled Garden Address list field