

TRB141 Internet Status

[Main Page](#) > [TRB Gateways](#) > [TRB141](#) > [TRB141 Manual](#) > [TRB141 WebUI](#) > [TRB141 Network section](#) > **TRB141 Internet Status**

The information in this page is updated in accordance with firmware version [TRB1_R_00.07.07.1](#).



Contents

- [1 Summary](#)
- [2 Status](#)
- [3 Configuration](#)

Summary

Internet status is a feature, also known as 'connchecker' which monitors the connectivity status of specified IPv4, IPv6, and DNS addresses. Repeatedly checks the connectivity status at specified intervals and reports changes.

If you're having trouble finding this page or some of the parameters described here on your device's WebUI, you should **turn on "Advanced WebUI" mode**. You can do that by clicking the "Advanced" button, located at the top of the WebUI.



Status



| Field | Value | Description |
|-------------|-------------------------------------|--|
| IPv4 status | Online Offline Untracked | <ul style="list-style-type: none">• Online - address is reachable.• Offline - address is unreachable.• Untracked - address not provided in the configuration or tracking is disabled. |
| IPv6 status | Online Offline Untracked | <ul style="list-style-type: none">• Online - address is reachable.• Offline - address is unreachable.• Untracked - address not provided in the configuration or tracking is disabled. |
| DNS status | Available Unavailable Untracked | <ul style="list-style-type: none">• Available - DNS is reachable.• Unavailable - DNS is unreachable.• Untracked - DNS not provided in the configuration or tracking is disabled. |

Configuration



| Field | Value | Description |
|--------------|--|--|
| Enable | off on; default: on | Enable internet monitoring. |
| Track IPv4 | ipv4; default: 1.1.1.1 | IPv4 address to be monitored. |
| Track IPv6 | ipv6; default: 2a00:1450:4001:831::200e | IPv6 address to be monitored. |
| Track domain | domain name; default: dns.google.com | Domain to be checked if alive. |
| Interval | seconds; default: 60 | The time interval in seconds at which the connectivity status should be checked. |