

TSW010 Power Consumption

[Main Page](#) > [TSW Switches](#) > [TSW010](#) > [TSW010 Manual](#) > **TSW010 Power Consumption**

TSW010 power consumption values in different states of operation are represented in the table(s) below:

| | Test type | Current (mA) | Power consumption (W) |
|-------------|-----------|--------------|-----------------------|
| Idle (9 V) | | 25 | 0.23 |
| Idle (24 V) | | 21 | 0.26 |
| Idle (24 V) | | 14 | 0.33 |

| | Test type | Current (mA) | Power consumption (W) |
|--|-----------|--------------|-----------------------|
| 2 LAN devices connected + heavy data traffic ¹ (9 V) | | 49 | 0.45 |
| 2 LAN devices connected + heavy data traffic ¹ (12 V) | | 39 | 0.47 |
| 2 LAN devices connected + heavy data traffic ¹ (24 V) | | 24 | 0.58 |

| | Test type | Current (mA) | Power consumption (W) |
|--|-----------|--------------|-----------------------|
| 5 LAN devices connected + heavy data traffic ¹ (9 V) | | 78 | 0.70 |
| 5 LAN devices connected + heavy data traffic ¹ (12 V) | | 61 | 0.73 |
| 5 LAN devices connected + heavy data traffic ¹ (24 V) | | 37 | 0.89 |

¹ - Data streams between devices were created using iPerf.

Power consumption may differ due to connected devices, testing environment and conditions.