

TSW200 Powering Options

[Main Page](#) > [TSW Switches](#) > [TSW200](#) > [TSW200 Manual](#) > **TSW200 Powering Options**

This chapter contains information on powering options supported by TSW200 switch.

□

Contents


- [1 Power socket](#)
 - [1.1 2 pin power socket](#)
- [2 Disclaimer: TSW200 and Passive PoE devices](#)

The switch has a 2 pin power socket and can be powered by a 7-57 VDC power supply unit (PSU). Refer to the image below for the power socket's pinout information:

Power socket

2 pin power socket

No.	Description	Wire color
1	Power	Red
2	Ground	Black



If you decide not to use the standard 50 VDC power supply unit and want to power the device with other voltages (7-57 VDC), please make sure that you choose a power supply of high quality. Some power supplies can produce voltage peaks significantly higher than the declared output voltage, especially during connection and disconnection.

While the device is designed to accept input voltage of up to 57 VDC peaks, high voltage power supplies can harm the device. If you want to use high voltage power supplies it is recommended to also use additional safety equipment to suppress voltage peaks from the power supply.

Note that TSW200 PoE ports works properly when switch is powered using PSU, which can supply 44 VDC or higher voltages. If TSW200 switch is powered with voltages ranging from 7 VDC to 43 VDC, it will work as standard switch, without PoE capabilities.

Disclaimer: TSW200 and Passive PoE devices

There are a couple of options to stay safe when using TSW200 **Active PoE** with devices that only support **Passive PoE**:

- Connect TSW200 and Passive PoE device only via non-PoE Ethernet ports (for example, **do not** use TSW200 PoE ports with **LAN1** ports on Teltonika devices).
- If there is a need to use **LAN1** port on the end device, make sure that TSW200 and the end

device are **powered from different voltage sources** (for example, power both devices from different PSUs, or different batteries).

If TSW200 and a Passive PoE device are connected with common ground, **do not use LAN1 port**, other ports can be used (refer to image below):

