

[https://wiki.teltonika-networks.com/view/Template:Networking\\_rut955\\_manual\\_input\\_output\\_post\\_get\\_examples\\_table](https://wiki.teltonika-networks.com/view/Template:Networking_rut955_manual_input_output_post_get_examples_table)

# Template:Networking rut955 manual input output post get examples table

Action	POST/GET URL
Turn relay output on	<a href="http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=on&amp;pin=relay">http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=on&amp;pin=relay</a>
Turn relay output on after a 10 second delay	<a href="http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=on&amp;pin=relay&amp;delay=10">http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=on&amp;pin=relay&amp;delay=10</a>
Turn relay output on for 5 seconds	<a href="http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=on&amp;pin=relay&amp;time=5">http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=on&amp;pin=relay&amp;time=5</a>
Turn Relay output on for 5 seconds after a 15 second delay	<a href="http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=on&amp;pin=relay&amp;delay=15&amp;time=5">http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=on&amp;pin=relay&amp;delay=15&amp;time=5</a>
Turn relay output off for 5 seconds after a 15 second delay	<a href="http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=off&amp;pin=relay&amp;delay=15&amp;time=5">http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=off&amp;pin=relay&amp;delay=15&amp;time=5</a>
Turn open collector output on	<a href="http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=on&amp;pin=oc">http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=on&amp;pin=oc</a>
Turn open collector output off	<a href="http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=off&amp;pin=oc">http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=off&amp;pin=oc</a>
Turn Digital 4 PIN output on	<a href="http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=on&amp;pin=4pin">http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=on&amp;pin=4pin</a>
Turn Digital 4 PIN output off	<a href="http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=off&amp;pin=4pin">http://192.168.1.1/cgi-bin/output?username=user1&amp;password=user1&amp;action=off&amp;pin=4pin</a>