RUT300 Power Consumption

 $\underline{Main\ Page} > \underline{RUT\ Routers} > \underline{RUT300} > \underline{RUT300\ Manual} > \textbf{RUT300\ Power\ Consumption}$

Averaged <u>RUT300</u> power consumption values in different states of operation are represented in the tables below:

Test type Idle (9 V) Idle (12 V) Idle (24 V)	Current (mA) 68 53 29	Power consumption (W) 0.61 0.64 0.70
Test type 2 LAN devices connected ¹ (9 V) 2 LAN devices connected ¹ (12 V) 2 LAN devices connected ¹ (24 V)	Current (mA) 114 86 45	Power consumption (W) 1.03 1.03 1.08
Test type	Current (mA)	Power consumption (W)
5 LAN devices connected 1 + high CPU load 2 + USB device connected 3 (9 V)	497	4.47
5 LAN devices connected 1 + high CPU load 2 + USB device connected 3 (12 V)	373	4.48
5 LAN devices connected 1 + high CPU load 2 + USB device connected 3 (24 V)	192	4.61

¹ - Data streams between RUT300 and other connected LAN devices created using iPerf.

Power consumption may differ due to mobile data transmission speed, testing environment and conditions.

² - Load created using *md5sum* (calculation and verification of 128-bit MD5 hashes).

 $^{^{\}scriptscriptstyle 3}$ - USB device with ~ 300 mA current draw.