

RUT300 Remote Monitoring & Administration

[Main Page](#) > [RUT Routers](#) > [RUT300](#) > [RUT300 Manual](#) > **RUT300 Remote Monitoring & Administration**

RUT300 supports multiple monitoring and administration possibilities.

□

Contents

- [1 Remote control options](#)
 - [1.1 RMS](#)
 - [1.2 Public IP](#)
 - [1.2.1 HTTP access](#)
 - [1.2.2 SSH access](#)
 - [1.3 JSON-RPC](#)
 - [1.4 VPN](#)
 - [1.5 SNMP](#)
 - [1.6 Modbus TCP](#)
 - [1.7 MQTT](#)
 - [1.8 TR-069](#)
 - [1.9 DNP3](#)
 - [1.10 OPC UA](#)

Remote control options

The RUT300 router supports the following remote control capabilities:

Remote control method	Can get parameters	Can set parameters
RMS	<input type="checkbox"/>	<input type="checkbox"/>
SSH	<input type="checkbox"/>	<input type="checkbox"/>
HTTP	<input type="checkbox"/>	<input type="checkbox"/>
JSON	<input type="checkbox"/>	<input type="checkbox"/>
VPN	<input type="checkbox"/>	<input type="checkbox"/>
SNMP	<input type="checkbox"/>	<input type="checkbox"/>
Modbus	<input type="checkbox"/>	<input type="checkbox"/>
MQTT	<input type="checkbox"/>	<input type="checkbox"/>
TR-069	<input type="checkbox"/>	<input type="checkbox"/>
DNP3	<input type="checkbox"/>	<input type="checkbox"/>
OPC UA	<input type="checkbox"/>	<input type="checkbox"/>

RMS

The **Remote Management System (RMS)** is designed to conveniently monitor and manage all your Teltonika networking devices. The system allows to securely gather status information of your devices and to change their configuration even if the devices do not have public IP addresses.

RMS access can be configured from the **System** → **Administration** → [RMS](#) page.

Public IP

If your device has a Public IP address (refer [here](#) for more information), you can reach the router via HTTP or SSH via its WAN IP address.

HTTP access

Remote **HTTP** access can be set up via the **System** → **Administration** → [Access Control](#) page.

SSH access

Remote **SSH** access can be set up via the **System** → **Administration** → [Access Control](#) page.

JSON-RPC

JSON-RPC access can be set up via the **System** → **Administration** → [Access Control](#) page.

VPN

Virtual Private Networks (VPNs) provide multiple flexible options on setting up remote access to the router and its LAN network. For more information on different types of VPNs supported by RUT300, visit the [VPN manual page](#).

SNMP

Simple Network Management Protocol (SNMP) is a protocol for network management, used for collecting information from network devices. For more information on SNMP in RUT300, visit the [SNMP manual page](#).

Modbus TCP

Modbus is a serial communications protocol used in communication with various types of industrial electronic devices. For more information on Modbus TCP in RUT300, visit the [Modbus manual page](#).

MQTT

MQTT (MQ Telemetry Transport or Message Queue Telemetry Transport) is a publish-subscribe-based "lightweight" messaging protocol for use on top of the TCP/IP protocol. For more information on MQTT in RUT300, visit the [MQTT manual page](#)

TR-069

Technical Report 069 (TR-069) is a technical specification of the Broadband Forum that defines an application layer protocol for remote management of customer-premises equipment (CPE) connected to an Internet Protocol (IP) network. For more information on TR-069 in RUT300, visit the [TR-069 manual page](#)

DNP3

Distributed Network Protocol 3 (DNP3) is a set of communications protocols used between components in process automation systems. For more information on DNP3 in RUT300, visit the [DNP3 manual page](#)

OPC UA

OPC Unified Architecture (OPC UA) is a cross-platform, open-source, IEC62541 standard for data exchange from sensors to cloud applications developed by the OPC Foundation. For more information on OPC UA in RUT300, visit the [OPC UA manual page](#)