

RUT301 Power Consumption

[Main Page](#) > [RUT Routers](#) > [RUT301](#) > [RUT301 Manual](#) > **RUT301 Power Consumption**

RUT301 power consumption values in different states of operation are represented in the table(s) below:

Test type	Current (mA)	Power consumption (W)
Idle (9 V)	59	0.53
Idle (12 V)	46	0.55
Idle (24 V)	31	0.744

Test type	Current (mA)	Power consumption (W)
2 LAN devices connected ¹ (9 V)	78	0.7
2 LAN devices connected ¹ (12 V)	62	0.74
2 LAN devices connected ¹ (24 V)	40	0.96

Test type	Current (mA)	Power consumption (W)
5 LAN devices connected ¹ + high CPU load ² + USB device connected ³ (9 V)	413	3.71
5 LAN devices connected ¹ + high CPU load ² + USB device connected ³ (12 V)	305	3.66
5 LAN devices connected ¹ + high CPU load ² + USB device connected ³ (24 V)	159	3.82

¹ - Data streams between RUT300 and other connected LAN devices created using iPerf.

² - Load created using *md5sum* (calculation and verification of 128-bit MD5 hashes).

³ - USB device with ~ 300 mA current draw.

Power consumption may differ due to mobile data transmission speed, testing environment and conditions.