RUT955 Power Consumption

 $\underline{\text{Main Page}} > \underline{\text{RUT Routers}} > \underline{\text{RUT955}} > \underline{\text{RUT955 Manual}} > \mathbf{RUT955 \ Power \ Consumption}$

<u>RUT955</u> power consumption values in different states of operation are represented in the table(s) below:

Idle, no SIM card inserted (9 V) Idle, no SIM card inserted (12 V) Idle, no SIM card inserted (24 V)	Test type	Current (mA) 201 168 87	Power consumption (W) 1.81 2.01 2.08
Idle + mobile data on ¹ (9 V) Idle + mobile data on ¹ (12 V) Idle + mobile data on ¹ (24 V)	Test type	Current (mA) 210 179 92	Power consumption (W) 1.89 2.15 2.21
Mobile data on 1 + 1 LAN device connected 2 (9 V) Mobile data on 1 + 1 LAN device connected 2 (12 V) Mobile data on 1 + 1 LAN device connected 2 (24 V)	Test type	Current (mA) 238 185 99	Power consumption (W) 2.14 2.22 2.38
Test type		Current (mA)	Power consumption (W)
Max speed LTE transmission + 4 LAN devices connected ² + high CPU load ³ + data transfer via WiFi + devices connected to RS485 and RS232 + GPS on + USB device connected ⁴ + all outputs enabled on I/O panel (9 V)		1020	9.18
Max speed LTE transmission + 4 LAN devices connected ² + high CPU load ³ + data transfer via WiFi + devices connected to RS485 and RS232 + GPS on + USB device connected ⁴ + all outputs enabled on I/O panel (12 V)		770	9.24
Max speed LTE transmission + 4 LAN devices connected ² + high CPU load ³ + data transfer via WiFi + devices connected to RS485 and RS232 + GPS on + USB device connected ⁴ + all outputs enabled on I/O panel (24 V)		386	9.26

¹ - Only mobile data connection established with no additional traffic.

Power consumption may differ due to mobile data transmission speed, testing environment and conditions.

² - Data streams between RUT955 and other connected LAN devices created using iPerf.

 $^{^{3}}$ - Load created using md5sum (calculation and verification of 128-bit MD5 hashes).

 $^{^{\}scriptscriptstyle 4}$ - USB device with ~ 300 mA current draw.