TSW110 First Start

 $\underline{\text{Main Page}} > \underline{\text{TSW Switches}} > \underline{\text{TSW110}} > \mathbf{TSW110}$ First Start

This Wiki page contains the online version of the **Quick Start Guide** (**QSG**) for the **TSW110 Switch**. Here you will find an overview of the various components found on the front and back sides of a TSW110 switch, basic hardware installation, device specifications and general safety information. It is highly recommended that you acquaint yourself with with the Quick Start Guide before using the device. If you own a TSW110 switch, you can also find a printed version of the Quick Start Guide in the device's package.



Contents

- 1 Front view
- 2 Back view
- 3 Connectors
- 4 Ethernet port
- <u>5 Safety information</u>

Front view

No.	Description	n
1	ETH LEDs	×
2	Ethernet port	

Back view

No.	Description	
1	4 pin power socket	
2	Power LED	
3	Grounding screw	×

Connectors

Ethernet port

No.	Action	Describtion	
1	Orange LED lit	10/100 Mbps link established	
1	Orange LED blinking	Active link connection	×
2	Green LED lit	1000 Mbps link established	

Safety information

TSW110 switch must be used in compliance with any and all applicable national and international laws and with any special restrictions regulating the utilization of the communication module in prescribed applications and environments.

Technical specifications

Input voltage range 7 - 30 VDC Max power consumption <5 W

Bundled accessories specifications*

Power adapter Input: AC/DC power adapter 9 V, 1 A, 4 pin plug

This sign on the package means that is necessary to read the User's Manual before you start using the device

This sign on the package means that all used electronic and electric equipment should not be mixed with general household waste

^{*} Order code dependant.