Template:Networking rut200 manual power consumption table

Idle, no SIM card inserted (9 V) Idle, no SIM card inserted (12 V) Idle, no SIM card inserted (24 V)	Test type	Current (mA) 118 96 51	Power consumption (W) 1.06 1.15 1.22
Idle + mobile data on ¹ (9 V) Idle + mobile data on ¹ (12 V) Idle + mobile data on ¹ (24 V)	Test type	Current (mA) 125 99 55	Power consumption (W) 1.16 1.19 1.32
Mobile data on 1 + 1 LAN device connected 2 (9 V) Mobile data on 1 + 1 LAN device connected 2 (12 V) Mobile data on 1 + 1 LAN device connected 2 (24 V)	Test type	Current (mA) 142 109 70	Power consumption (W) 1.29 1.31 1.68
Test type 2 LAN devices connected ² + high CPU load ³ + max speed LTE transmission + data transfer via WiFi (9 V) 2 LAN devices connected ² + high CPU load ³ + max speed LTE transmission + data transfer via WiFi (12 V) 2 LAN devices connected ² + high CPU load ³ + max speed LTE transmission + data transfer via WiFi (24 V)		Current (mA) 426 318 161	Power consumption (W) 3.83 3.82 3.86

 $^{^{\}scriptscriptstyle 1}$ - Only mobile data connection established with no additional traffic.

Power consumption may differ due to mobile data transmission speed, testing environment and conditions.

 $^{^{\}scriptscriptstyle 2}$ - Data streams between RUT200 and other connected LAN devices created using iPerf.

³ - Load created using *md5sum* (calculation and verification of 128-bit MD5 hashes).