

Template:Networking rut200 manual supported frequency bands table

Product code	Region (operator)	Supported bands
RUT200 *0****	The Middle East, Africa	• 4G (LTE-FDD): B1 (2100 MHz), B3 (1800 MHz), B5 (850 MHz), B7 (2600 MHz), B8 (900 MHz), B20 (800 MHz) • 4G (LTE-TDD): B40 (2300 MHz) • 3G: B1 (2100 MHz), B5 (850 MHz), B8 (900 MHz) • 2G: B3 (1800 MHz), B8 (900 MHz)
RUT200 *1****	Europe ¹ , Asia-Pacific	• 4G (LTE-FDD): B1 (2100 MHz), B3 (1800 MHz), B5 (850 MHz), B7 (2600 MHz), B8 (900 MHz), B20 (800 MHz), B28 (700 MHz) • 4G (LTE-TDD): B38 (2600 MHz), B40 (2300 MHz), B41 (2500 MHz) • 3G: B1 (2100 MHz), B5 (850 MHz), B8 (900 MHz) • 2G: B3 (1800 MHz), B8 (900 MHz)
RUT200 *2****	Australia, New Zealand, Latin America	• 4G (LTE-FDD): B1 (2100 MHz), B2 (1900 MHz), B3 (1800 MHz), B4 (1700 MHz), B5 (850 MHz), B7 (2600 MHz), B8 (900 MHz), B28 (700 MHz), B66 (1700 MHz) • 4G (LTE-TDD): B40 (2300 MHz) • 3G: B1 (2100 MHz), B2 (1900 MHz), B4 (1700 MHz), B5 (850 MHz), B8 (900 MHz) • 2G: B2 (1900 MHz), B3 (1800 MHz), B5 (850 MHz), B8 (900 MHz)

¹ Regional availability - excluding Russia & Belarus.