

# Template:Networking rutx09 manual product labels

The information in this page is relevant from {{{batch}}} batch.



## Label/Print on the box

[[File:Networking {{{name}}} first start dezutes lipdukas v2.png|400px]]

Information displayed after scanning QR code: <span>{{{boxqr}}}</span> [[File:Networking <span>{{{name}}}</span> first start dezutes QR v1.jpg 250px]]	Information displayed after scanning SN Barcode: 9999999999	Information displayed after scanning Barcode: <span>{{{ean}}}</span> [[File:Networking <span>{{{name}}}</span> first start dezutes barcode v1.jpg 250px]]
Text on the label/print	QR or Barcode equivalent	Description
<span>{{{standart code}}}</span> *	-	Product code a.k.a., ordering code, displays under which product code the device was manufactured. Different product codes indicate different versions of the overall product. For example, devices with different product codes may support different LTE bands, come with different accessories, different firmware, etc. <b><span>{{{standart code}}}</span></b> is only for standard order codes
SERIAL	SN	Serial number is a unique 10-digit device identifier. It is required when connecting the device to Teltonika's Remote Management System ( <a href="#">RMS</a> ). The device can be added to RMS via the <b>System → Administration → <a href="#">RMS</a></b> page
IMEI	I	The IMEI (International Mobile Equipment Identity) is a unique 15 decimal digit number used to identify cellular modules. GSM network operators use the IMEI to identify devices in their networks
LAN MAC	M	The media access control (MAC) address is a unique identifier used to distinguish a network interface controller for communication in the data link layer (OSI layer2) Ethernet LAN MAC address - MAC address of the LAN Ethernet network interface. It is also required when connecting the device to Teltonika's Remote Management System ( <a href="#">RMS</a> ). The device can be added to RMS via the <b>System → Administration → <a href="#">RMS</a></b> page
EAN	-	The International Article Number (a.k.a. European Article Number or <a href="#">EAN</a> ) is a standard describing a barcode symbology and numbering system used in global trade to identify a specific retail product type, in a specific packaging configuration, from a specific manufacturer
BATCH NO:	B	Batch number is a number that indicates the batch of materials

## Label on the product

[[File:Networking\_{{{name}}}\_first\_start\_gaminio\_lipdukas\_v3.png|400px]]

Information displayed after scanning QR code: {{{productqr}}}		Information displayed after scanning SN Barcode: 9999999999	
			
Text on the sticker	QR or Barcode equivalent	Description	
SERIAL	SN	Serial number is a unique 10-digit device identifier. It is required when connecting the device to Teltonika's Remote Management System ( <a href="#">RMS</a> ). The device can be added to RMS via the <b>System → Administration → <a href="#">RMS</a></b> page	
IMEI	I	The IMEI (International Mobile Equipment Identity) is a unique 15 decimal digit number used to identify cellular modules. GSM network operators use the IMEI to identify devices in their networks	
LAN MAC	M	The media access control (MAC) address is a unique identifier used to distinguish a network interface controller for communication in the data link layer (OSI layer2) Ethernet LAN MAC address - MAC address of the LAN Ethernet network interface. It is also required when connecting the device to Teltonika's Remote Management System ( <a href="#">RMS</a> ). The device can be added to RMS via the <b>System → Administration → <a href="#">RMS</a></b> page	
USERNAME	U	A default value "admin" is used for product connection	
PASSWORD	PW	A custom passphrase used for product connection (at least 8 characters long)	
BATCH NO:	B	Batch number is a number that indicates the batch of materials	

[[Category:{{{NAME}}}\_Manual]]