Template:Networking rutx12 manual product labels

The information in this page is relevant from **{{batch}}}** batch.

Label/Print on the box

[[File:Networking {{{name}}}} first start dezutes lipdukas v2.png|400px]]

Information displayed after scanning QR code:		Information displayed after scanning SN Barcode:	Information displayed after scanning Barcode:
{{{boxqr}}}		999999999	{{{ean}}}
[[File:Networking $\{\{\{name\}\}\}\$ first start dezutes QR v1.jpg[250px]]		×	[[File:Networking $\{\{\{name\}\}\}\$ first start dezutes barcode v1.jpg[250px]]
Text on the label/print	QR or Barcode equivale	nt Des	cription
{{{standart code}}}*	-		
SERIAL	SN		it is required when connecting the device to Teltonika's be added to RMS via the $\mathbf{System} \to \mathbf{Administration} \to$
IMEI1 or IMEI2	I1 or I2	The IMEI (International Mobile Equipment Identity) is cellular modules. GSM network operators use the IM	
LAN MAC	М		
EAN	-		rticle Number or <u>EAN</u>) is a standard describing a barcode de to identify a specific retail product type, in a specific er
BATCH NO:	В	Batch number is a number that indicates the batch of	f materials

Label on the product

[[File:Networking {{{name}}}}_first_start_gaminio_lipdukas_v3.png|400px]]

Information displayed after scanning QR code: Information displayed after scanning SN Barcode: $\{\{\text{productqr}\}\} \\ [\text{File:Networking}_{\{\{\text{name}\}\}_{\text{first_start_gaminio}}QR_v1.jpg|250px]}] \\ \blacksquare$

Scanning the QR code with your mobile device should allow you to connect to the products WiFi.

Text on the sticker	QR or Barcode equivalent	Description
SERIAL	SN	Serial number is a unique 10-digit device identifier. It is required when connecting the device to Teltonika's Remote Management System (\underline{RMS}). The device can be added to RMS via the $\underline{System} \rightarrow \underline{Administration} \rightarrow \underline{RMS}$ page
IMEI1 or IMEI2	I1 or I2	The IMEI (International Mobile Equipment Identity) is a unique 15 decimal digit number used to identify cellular modules. GSM network operators use the IMEI to identify devices in their networks
LAN MAC	M	The media access control (MAC) address is a unique identifier used to distinguish a network interface controller for communication in the data link layer (OSI layer2) Ethernet LAN MAC address - MAC address of the LAN Ethernet network interface. It is also required when connecting the device to Teltonika's Remote Management System (RMS). The device can be added to RMS via the $\mathbf{System} \to \mathbf{Administration} \to \mathbf{RMS}$ page
SSID 2.4GHz or 5GHz	S	The broadcasted SSID (Service Set Identifier) of the wireless network
WIFI PASSWORD	P	A custom passphrase used for authentication (at least 8 characters long)
USERNAME	U	A default value "admin" is used for product connection
PASSWORD	PW	A custom passphrase used for product connection (at least 8 characters long)
BATCH NO:	В	Batch number is a number that indicates the batch of materials

 $[[Category: \{\{\{NAME\}\}\}_Manual]]$