

Template:Networking trb140 manual supported frequency bands table

Product code	Region (operator) ¹	Supported bands
TRB140 0 ****	Europe ² , the Middle East, Africa, Korea, Thailand, India, Malaysia	• 4G (LTE-FDD): B1 (2100 MHz), B3 (1800 MHz), B7 (2600 MHz), B8 (900 MHz), B20 (800 MHz), B28A (700 MHz) • 4G (LTE-TDD): B38 (2600 MHz), B40 (2300 MHz), B41 (2500 MHz) • 3G: B1 (2100 MHz), B8 (900 MHz) • 2G: B3 (1800 MHz), B8 (900 MHz)
TRB140 1 ****	South America, Australia, New Zealand, Taiwan, Malaysia	• 4G (LTE-FDD): B1 (2100 MHz), B2 (1900 MHz), B3 (1800 MHz), B4 (1700 MHz), B5 (850 MHz), B7 (2600 MHz), B8 (900 MHz), B28 (700 MHz) • 4G (LTE-TDD): B40 (2300 MHz) • 3G: B1 (2100 Mhz), B2 (1900 Mhz), B5 (850 Mhz), B8 (900 MHz) • 2G: B2 (1900 MHz), B3 (1800 MHz), B5 (850 MHz), B8 (900 MHz)

¹ Versions for other regions are under development.

² Regional availability - excluding Russia & Belarus.