

Template:Networking trb245 manual supported frequency bands table

Product code	Region (operator)	Supported bands
TRB245 0*****	Europe ² , the Middle East, Africa, Thailand	• 4G (LTE-FDD): B1 (2100 MHz), B3 (1800 MHz), B7 (2600 MHz), B8 (900 MHz), B20 (800 MHz), B28A (700 MHz) • 4G (LTE-TDD): B38 (2600 MHz), B40 (2300 MHz), B41 (2500 MHz) • 3G: B1 (2100 MHz), B8 (900 MHz) • 2G: B3 (1800 MHz), B8 (900 MHz)
TRB245 1*****	North America	• 4G (LTE-FDD): B2 (1900 MHz), B4 (1700 MHz), B5 (850 MHz), B12 (700 MHz), B13 (700 MHz), B14 (700 MHz), B66 (1700/2100 MHz), B71 (600 MHz) • 3G: B2 (1900 MHz), B4 (1700 MHz), B5 (850 MHz)
TRB245 2*****	Latin America, Australia, New Zealand	• 4G (LTE-FDD): B1 (2100 MHz), B2¹ (1900 MHz), B3 (1800 MHz), B4 (1700 MHz), B5 (850 MHz), B7 (2600 MHz), B8 (900 MHz), B28 (700 MHz) • 4G (LTE-TDD): B40 (2300 MHz) • 3G: B1 (2100 Mhz), B2 (1900 Mhz), B5 (850 Mhz), B8 (900 MHz) • 2G: B2 (1900 MHz), B3 (1800 MHz), B5 (850 MHz), B8 (900 MHz)
TRB245 3*****	China	• 4G (LTE-FDD): B1 (2100 MHz), B3 (1800 MHz) • 4G (LTE-TDD): B38 (2600 MHz), B39 (1900 MHz), B40 (2300 MHz), B41 (2500 MHz) • 3G (TDSCDMA): B34 (2100 MHz), B39 (1900 MHz) • 3G (WCDMA): B1 (2100 MHz) • 3G (CDMA 1x/EVDO): BC0 (800 MHz) • 2G: B2 (1900 MHz), B8 (900 MHz)

¹ LTE-FDD B2 does not support Rx-diversity.

² Regional availability - excluding Russia & Belarus.