## Template:Networking trb manual product labels

The information in this page is relevant from **{{batch}}}** batch.

## Label/Print on the box

[[File:Networking {{{name}}}} first start dezutes lipdukas v2.png|400px]]

lem:lem:lem:lem:lem:lem:lem:lem:lem:lem:		Information displayed after scanning SN Barcode: 99999999999	lem:lem:lem:lem:lem:lem:lem:lem:lem:lem:
Text on the label/print	QR or Barcode equivalen	Description	
{{{standart code}}}*	-	Product code a.k.a., ordering code, displays under which product code the device was manufactured. Different product codes indicate different versions of the overall product. For example, devices with different product codes may support different LTE bands, come with different accessories, different firmware, etc.  *{{{standart code}}} is only for standard order codes	
SERIAL	SN	Serial number is a unique 10-digit device identifier. It is required when connecting the device to Teltonika's Remote Management System ( $\underline{RMS}$ ). The device can be added to RMS via the $\underline{System} \rightarrow \underline{Administration} \rightarrow \underline{RMS}$ page	
IMEI	I	The IMEI (International Mobile Equipment Identity) is a unique 15 decimal digit number used to identify cellular modules. GSM network operators use the IMEI to identify devices in their networks	
EAN	-	The International Article Number (a.k.a. European Article Number or <u>EAN</u> ) is a standard describing a barcode symbology and numbering system used in global trade to identify a specific retail product type, in a specific packaging configuration, from a specific manufacturer	
BATCH NO:	В	Batch number is a number that indicates the batch of	materials

## Label on the product



. ,			Information displayed after scanning SN Barcod 9999999999 pg[250px]]	e:
Text on the	sticker	QR or Barcode equivalent	Description	
SERIAL		SN	Serial number is a unique 10-digit device identifier. It is required when connecting the device to Teltonika's Remote Management System ( $\underline{RMS}$ ). The device can be added to RMS via the <b>System</b> $\rightarrow$ <b>Administration</b> $\rightarrow$ $\underline{RMS}$ page	
IMEI		I	The IMEI (International Mobile Equipment Identity) is a unique 15 decimal digit number used to identify cellular modules. GSM network operators use the IMEI to identify devices in their networks	
USERNAME		U	default value "admin" is used for product connection	
PASSWORD		PW	custom passphrase used for product connection (at least 8 characters lo	ng)
BATCH NO:		В	atch number is a number that indicates the batch of materials	

[[Category:{{{NAME}}} Manual]]